

Questions and answers Procurement procedure: Specialized intervention equipment

Contracting Authority: Ministry of Interior of the Republic of Serbia

Ref.no. RORS00005 - TD03/R

OJ reference: OJ S 249/2024 23/12/2024

TED Notice Number: 787623-2024

No	Question	Answer
1	FIRE AND RESCUE TRUCK - Point 14.6, requirement 103.	To further increase fair competition and encourage greater participation from various manufacturers, we will adjust the specifications for this item.
	Since the requirements related to the cutters are met by one manufacturer, we propose that the weight of the battery-operated cutters with battery be a maximum of 25kg. Confirm that the cutter with a weight of a maximum of 25kg including battery will be acceptable.	170 mm, and the maximum weight will be increased from 18 kg to 19 kg.

Sector for Emergency Management

2	FIRE AND RESCUE TRUCK - Point 14.6, requirement 103. Since the requirements related to the force and weight of the spreaders are met by one manufacturer, we believe that for the transparency of the tender, other manufacturers should also be allowed to participate in the tender. We propose that the spreading force be at least 500kN and that the weight of the battery-operated spreader including the battery is a maximum of 21kg. Confirm that the spreader with a spreading force of at least 500kN and a weight of a maximum of 21kg will be acceptable.	The proposed changes of spreaders characteristics can not be accepted. According to market research, there are at least 2 world-known manufacturers of spreaders that can meet requested characteristics.
3	FIREFIGHTING WATER TENDER TRUCK- Point 11.5 requirement 103. Since the requirements related to the force and weight of the spreaders are met by one manufacturer, we believe that for the transparency of the tender, other manufacturers should also be allowed to participate in the tender. We propose that the spreading force be at least 500kN and that the weight of the battery-operated spreader including the battery is a maximum of 21kg. Confirm that the spreader with a spreading force of at	The proposed changes of spreaders characteristics can not be accepted. According to market research, there are at least 2 world-known manufacturers of spreaders that can meet requested characteristics.



Sector for Emergency Management

	least 500kN and a weight of a maximum of 21kg will be acceptable.	
4	FIRE AND RESCUE TRUCK-Point 14.3., requirement 93: To enhance competition, we propose revising the requirements to: - Adjustable light height from min 1m to min 1.8m. - Inclusion of two Li-Ion batteries with a minimum of 7.5 hours of operating autonomy. Focusing on autonomy, rather than battery capacity (Ah), ensures practical performance without excluding other manufacturers. This change would allow alternative superstructure providers to compete, fostering broader participation.	Fire and Rescue Units serve as the first responders to a diverse range of emergencies, whether in open areas, buildings, or confined spaces. This requirement enhances their operational flexibility and effectiveness thus adjustable light height from minimum 1m to minimum 1.8m cannot be accepted. Battery amperage is a critical feature that guarantees operational stability during peak workloads while also supporting fast recharging capabilities thus cannot be accepted.
5	In the ANNEX II + III: TECHNICAL SPECIFICATIONS + TECHNICAL OFFER Fire and rescue truck on page 4 item number 2 you are asking that transmission should be manual minimum 8 + 1 speed.	We acknowledge the typo error. The transmission for Fire and rescue truck should be either automatic or manual, with a minimum of 8+1 speeds.



Sector for Emergency Management

	On page 21, Firefighting water tender trucks you are asking that transmission should be manual or automatic minimum 8+1 speed. Since you are allowing for one type of truck manual or automatic transmission, is it allowed to offer automatic transmission for Fire and rescue truck?	
6	For the Fire and rescue truck in the equipment on page 18 you are asking hand held thermal camera with display min 3" LED and for the Firefighting water tender truck on page 34 you are asking thermal camera with display min 4". Is it allowed to offer camera with display 3.5" with better resolution?	inches, provided that all other specifications meet the required standards.

Clarifications of the tender dossier (questions and answers) and Corrigendum of TECHNICAL SPECIFICATIONS were published on:

- $\hbox{- the official website of Interreg IPA CBC Romania-Serbia\ Programme\ on\ the\ following\ link:}$
- https://romaniaserbia.net/transparency/publicprocurements/
- the official website of the Ministry of Interior of the Republic of Serbia on the following link:

http://www.mup.gov.rs/wps/portal/sr/finansije/Konkursi